

LEED Pilot Credit Library

Pilot Credit 34: Design for Adaptability

Pilot Credit 34: Design for Adaptability

Applicable Rating Systems >> Requirements >> Submittals >> Additional Questions >> Background Information >> Changes >>

Applicable Rating Systems

This credit is available for pilot testing by the following LEED project types:

- Homes
- Mid-Rise

Intent

To reduce the materials needed for and waste produced from future maintenance, repair, renovation and rehabilitation through structural, mechanical, and user-induced design.

Requirements

HOMES

Note: Multi-family projects required to meet the Fair Housing Amendments Act (FHAA) (e.g., a building with \geq 4 residential units and an elevator) may earn points in Option 1 if they have twice the number of accessible units that meet FHAA requirements than what is required by code.

Option 1: Universal Design Features. Meet all of the following:

- 1. Zero-Step Main Entrance: Entrances with no abrupt change in level must provide access to dwelling units and site amenities.
- 2. Accessible Doorway: A doorway must have a minimum clear width of open doorway of 32 inches and clear maneuvering space inside and outside the door.
- 3. Accessible Passage: An accessible route is a path that is at least 36 inches wide, smooth, as level as possible, and without hazards or obstructions.
- 4. Adaptable bathroom: Bathroom must have a minimum 30 inch x 48 inch clear floor space and standard accessible shower and toilet fixtures.
- 5. Accessible HVAC and lighting controls: Controls such as thermostats and other heating, air-conditioning, and ventilation mechanisms as well as light switches and electrical outlets must be positioned no less that 15 inches from the floor and no higher than 48 inches with no access obstructions.
- 6. A kitchen, dining area, living area, adaptable full bathroom, and bedroom on the accessible level.



LEED Pilot Credit Library

Pilot Credit 34: Design for Adaptability

AND/OR

OPTION 2: Open Building Structural Systems Allow for easy redefining of rooms/floorplans with minimal renovation and material waste. Meet both of the following:

- 1. Centralized primary structural elements (such as "clear-span" structural design and partitions)
- 2. Flexible ceiling or floor systems (such as suspended ceilings, open-web floor trusses, raised or plenum floors)

AND/OR

Option 3. Organized and accessible MEP systems Meet one of the following:

- Stacked plumbing, electrical and mechanical design. Stacked or adjacent MEP layouts locate functional areas (like bathrooms, kitchens, and laundry areas for plumbing lines) vertically from floor to floor or in shared common walls on the same floor to provide access for installation and repairs, reduce redundant supply and space requirements, and ensure adaptable use of non-MEP spaces
- 2. Separation of MEP systems from within exterior walls and primary interior structural members

MID-RISE

Projects required to meet the Fair Housing Amendments Act (FHAA) (e.g., a building with \geq 4 residential units and an elevator) may earn points in if they have twice the number of accessible units that meet FHAA requirements than what is required by code.

Universal Design Features (1 point) Meet all of the following:

- 1. Zero-Step Main Entrance: Entrances with no abrupt change in level must provide access to dwelling units and site amenities.
- 2. Accessible Doorway: A doorway must have a minimum clear width of open doorway of 32 inches and clear maneuvering space inside and outside the door.
- 3. Accessible Passage: An accessible route is a path that is at least 36 inches wide, smooth, as level as possible, and without hazards or obstructions.
- 4. Adaptable bathroom: Bathroom must have a minimum 30 inch x 48 inch clear floor space and standard accessible shower and toilet fixtures.
- 5. Accessible HVAC and lighting controls: Controls such as thermostats and other heating, air-conditioning, and ventilation mechanisms as well as light switches and electrical outlets must be positioned no less that 15 inches from the floor and no higher than 48 inches with no access obstructions.
- 6. A kitchen, dining area, living area, adaptable full bathroom, and bedroom on the accessible level.



LEED Pilot Credit Library

Pilot Credit 34: Design for Adaptability

Credit Submittals

General:

- 1. <u>Register for Pilot Credit(s) here</u>.
- 2. Register a username at <u>LEEDuser.com</u>, and participate in online forum
- 3. <u>Submit feedback survey</u>; supply PDF of your survey/confirmation of completion with credit documentation

Credit Specific:

- List exactly which measures were installed
- Sign off by the green rater sign off that the measures were installed in each unit.

Additional Questions

- Why were the specific measures that were installed chosen?
- Were additional measures not included in this credit, with the intent of improving universal design or minimizing the waste from future modifications installed? If so, what were they?

Background Information

Waste from demolition and remodeling accounts for a significant portion of what goes into landfill. Designing for future use and modifications can reduce the intrusiveness of renovations, significantly reducing the future waste.

Changes

Changes made for 2nd Public Comment (08/01/2011):

- Drastically simplified the requirements of each of the low-rise options.
- For Mid-Rise, limited credit availability to only Universal Design