



## Tree-Lined and shaded streets

LT9 | Possible point

Glossary

### Intent

To encourage walking, bicycling, and transit use and discourage excessive motoring speeds. To reduce urban heat island effects, improve air quality, increase evapotranspiration, and reduce cooling loads in buildings.

To encourage walking and bicycling and discourage speeding. To reduce urban heat island effects, improve air quality, increase evapotranspiration, and reduce cooling loads in buildings.

### Requirements

#### Option 1. Tree-lined streets (1 point)

Design and build the project to provide street trees on both sides of at least 60% of new and existing streets within the project and on the project side of bordering streets, between the vehicle travel way and walkway, at intervals averaging no more than 40 feet (12 meters) (excluding driveways and utility vaults).

#### AND/OR

#### Option 2. Shaded streets (1 point)

Trees or other structures provide shade over at least 40% of the length of sidewalks on streets within or contiguous to the project. Trees must provide shade within ten years of landscape installation. Use the estimated crown diameter (the width of the shade if the sun is directly above the tree) to calculate the shaded area.

#### AND

#### For all projects involving street tree plantings

Obtain a registered landscape architect's determination that planting details are appropriate to growing healthy trees, taking into account tree species, root medium, and width and soil volume of planter strips or wells, and that the selected tree species are not considered invasive in the project context according to USDA or the state agricultural extension service.

#### Option 1. tree-lined blocks (1 point)

Provide trees at intervals of no more than 50 feet (12 meters) (exempting driveways) along at least 60% of the total existing and planned block length within the project, and on the project side of blocks bordering the project, between the vehicle travel way (if there is one) and walkway). Alleys may be exempted from the block length calculations.

#### AND/OR

#### Option 2. shaded sidewalks (1 point)

Provide shade from trees or permanent structures over at least 40% of the total length of existing and planned sidewalks within or bordering the project (alleys may be exempted). Trees must provide shade within 10 years of landscape installation. Use the estimated crown diameter to calculate the length of sidewalk shaded.

#### AND

#### For all projects with street tree plantings

From a registered landscape architect (or local equivalent for projects outside the U.S.), obtain a determination that planting details are appropriate to growing healthy trees, taking into account tree species, root medium, and width and soil volume of planter strips or wells, and that the selected tree species are not considered invasive in the project context according to USDA or the state agricultural extension service (or local equivalent for projects outside the U.S.).