

- [EQ117 | Interior lighting](#)
- [EQ118 | Interior lighting](#)
- [EQ119 | Interior lighting](#)
- [EQ120 | Interior lighting](#)
- [EQ120 | Interior lighting](#)
- [EQ121 | Daylight](#)
- [EQ121 | Daylight](#)
- [EQ121 | Daylight](#)
- [EQ121 | Daylight](#)
- [EQ122 | Daylight and quality views](#)
- [EQ122 | Daylight and quality views](#)
- [EQ122 | Daylight and quality views](#)
- [EQ123 | Quality views](#)
- [EQ124 | Acoustic performance](#)
- [EQ124 | Acoustic performance](#)
- [EQ125 | Green cleaning - custodial effectiveness assessment](#)
- [EQ126 | Green cleaning - products and materials](#)
- [EQ127 | Green cleaning - equipment](#)
- [EQ128 | Integrated pest management](#)
- [EQ129 | Occupant comfort survey](#)
- [EQ131 | Acoustic Performance](#)
- [EQ2.1 | Construction indoor air quality management plan](#)
- [EQ2.2 | Construction indoor air quality assessment](#)
- [EQ3.1 | High performance green cleaning program](#)
- [EQ3.2 | Custodial effectiveness assessment](#)
- [EQ3.3 | Sustainable purchasing of cleaning products and materials](#)
- [EQ3.4 | Sustainable purchasing of cleaning equipment](#)
- [EQ3.5 | Indoor chemical and pollutant source control](#)
- [EQ3.6 | Indoor integrated pest management](#)
- [EQ4 | Low-emitting interiors](#)
- [EQ5.1 | Occupant comfort survey](#)
- [EQ5.2 | Documenting productivity impacts](#)
- [EQ6.1 | Thermal comfort - design](#)
- [EQ6.2 | Thermal comfort - controllability](#)
- [EQ6.3 | Thermal comfort - verification](#)
- [EQ6.4 | Mold prevention](#)
- [EQ7.1 | Interior lighting - design](#)
- [EQ7.2 | Interior lighting - controllability](#)
- [EQ8 | Daylight](#)
- [EQ9 | Quality views](#)
- [EQ907 | Acoustic performance](#)
- [EQc1 | EPA Indoor airPLUS](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Carbon dioxide \(CO2\) monitoring](#)
- [EQc1 | Carbon dioxide \(CO2\) monitoring](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Enhanced ventilation](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1.1 | Indoor air quality best management practices - indoor air quality management program](#)
- [EQc1.1 | IAQ best management practices - IAQ management program](#)
- [EQc1.2 | Indoor air quality best management practices - outdoor air delivery monitoring](#)
- [EQc1.2 | IAQ best management practices - outdoor air delivery monitoring](#)
- [EQc1.3 | Indoor air quality best management practices - increased ventilation](#)
- [EQc1.3 | IAQ best management practices - increased ventilation](#)
- [EQc1.4 | Indoor air quality best management practices - reduce particulates in air distribution](#)
- [EQc1.4 | IAQ best management practices - reduce particulates in air distribution](#)
- [EQc1.5 | Indoor air quality best management practices - indoor air quality management for facility additions and alterations](#)
- [EQc1.5 | IAQ best management practices - management for facility alterations and additions](#)
- [EQc10 | Garage pollutant protection](#)
- [EQc10 | Mold prevention](#)
- [EQc10 | Mold prevention](#)
- [EQc10.1 | Green cleaning - entryway systems](#)
- [EQc10.2 | Green cleaning - isolation of janitorial closets](#)
- [EQc10.3 | Green cleaning - low environmental impact cleaning policy](#)
- [EQc10.4 | Green cleaning - low environmental impact pest management policy](#)
- [EQc10.5 | Green cleaning - low environmental impact pest management policy](#)
- [EQc10.6 | Green cleaning - low environmental impact cleaning equipment policy](#)
- [EQc2 | Combustion venting](#)
- [EQc2 | Acoustic environment](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Ventilation effectiveness](#)
- [EQc2 | Increase ventilation effectiveness](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Contaminant control](#)
- [EQc2 | Contaminant control](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2.1 | Occupant comfort - occupant survey](#)

- EQc4.4 | [Low-emitting materials - composite wood and agrifiber products](#)
- EQc4.4 | [Low-emitting materials - composite wood and agrifiber products](#)
- EQc4.5 | [Low-emitting materials - systems furniture and seating](#)
- EQc4.5 | [Low-emitting materials - systems furniture and seating](#)
- EQc4.5 | [Low-emitting materials - furniture](#)
- EQc4.6 | [Low-emitting materials - ceiling and wall systems](#)
- EQc5 | [Local exhaust](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical & pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical & pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Enhanced combustion venting](#)
- EQc5 | [Enhanced combustion venting](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5 | [Indoor chemical and pollutant source control](#)
- EQc5.1 | [Indoor chemical and pollutant source control - non-cleaning system reduce particulates in air distribution](#)
- EQc5.2 | [Indoor chemical and pollutant source control - non-cleaning - isolation of high-volume copying/print rooms/fax stations](#)
- EQc6 | [Controllability of systems - thermal comfort](#)
- EQc6 | [Distribution of space heating and cooling](#)
- EQc6 | [Controllability of systems - thermal comfort](#)
- EQc6 | [Controllability of systems - lighting and thermal comfort](#)
- EQc6 | [Controllability of systems - lighting and thermal comfort](#)
- EQc6 | [Enhanced garage pollutant protection](#)
- EQc6 | [Enhanced garage pollutant protection](#)
- EQc6 | [Controllability of systems - thermal comfort](#)
- EQc6.1 | [Controllability of systems - lighting](#)
- EQc6.1 | [Lighting system design & controllability](#)
- EQc6.1 | [Controllability of systems - perimeter spaces](#)
- EQc6.1 | [Controllability of systems - perimeter spaces](#)
- EQc6.1 | [Controllability of systems: lighting and thermal comfort](#)
- EQc6.1 | [Controllability of systems - lighting](#)
- EQc6.2 | [Controllability of systems - thermal comfort](#)
- EQc6.2 | [Controllability of systems - temperature and ventilation](#)
- EQc6.2 | [Controllability of systems - temperature and ventilation](#)
- EQc6.2 | [Thermal comfort controllability](#)
- EQc6.2 | [Controllability of systems - non-perimeter spaces](#)
- EQc6.2 | [Controllability of systems - non-perimeter spaces](#)
- EQc6.2 | [Controllability of systems - thermal comfort](#)
- EQc6.2 | [Controllability of systems - thermal comfort](#)
- EQc6.2 | [Controllability of systems - thermal comfort](#)
- EQc6.2 | [Controllability of systems - thermal comfort](#)
- EQc6.2 | [Controllability of systems - thermal comfort](#)
- EQc7 | [Air filtering](#)
- EQc7 | [Thermal comfort - design](#)
- EQc7 | [Thermal comfort - design](#)
- EQc7 | [Thermal comfort - design and verification](#)
- EQc7 | [Low-emitting products](#)
- EQc7 | [Low-emitting products](#)
- EQc7 | [Thermal comfort - design](#)
- EQc7.1 | [Thermal comfort - design](#)
- EQc7.1 | [Thermal comfort - design](#)
- EQc7.1 | [Thermal comfort - compliance](#)
- EQc7.1 | [Thermal comfort - compliance](#)
- EQc7.1 | [Thermal comfort: design](#)
- EQc7.1 | [Thermal comfort - compliance with ASHRAE 55-1992](#)
- EQc7.1 | [Thermal comfort - compliance with ASHRAE 55-1992](#)
- EQc7.1 | [Thermal comfort: design](#)
- EQc7.1 | [Thermal comfort: compliance](#)
- EQc7.1 | [Thermal comfort - design](#)
- EQc7.1 | [Thermal comfort - design](#)
- EQc7.1 | [Thermal comfort - design](#)
- EQc7.2 | [Thermal comfort - verification](#)
- EQc7.2 | [Thermal comfort - employee verification](#)
- EQc7.2 | [Thermal comfort - verification](#)
- EQc7.2 | [Thermal comfort - monitoring](#)
- EQc7.2 | [Thermal comfort - permanent monitoring system](#)
- EQc7.2 | [Thermal comfort: verification](#)
- EQc7.2 | [Thermal comfort - permanent monitoring system](#)
- EQc7.2 | [Thermal comfort - permanent monitoring system](#)
- EQc7.2 | [Thermal comfort - verification](#)
- EQc7.2 | [Thermal comfort - verification](#)
- EQc7.2 | [Thermal comfort - employee verification](#)
- EQc7.2 | [Thermal comfort: employee verification](#)
- EQc7.2 | [Thermal comfort, employee verification](#)
- EQc7.2 | [Thermal comfort - verification](#)
- EQc8 | [Contaminant control](#)
- EQc8 | [No environmental tobacco smoke](#)
- EQc8.1 | [Daylight and views - daylight](#)

- o [EQp4 | Radon-resistant construction](#)
- o [EQp4.1 | Asbestos removal or encapsulation](#)
- o [EQp4.1 | Hazardous material removal or encapsulation](#)
- o [EQp4.2 | Polychlorinated biphenyl removal](#)
- o [EQp5 | Air filtering](#)
- o [EQp6 | Environmental tobacco smoke](#)
- o [EQp7 | Compartmentalization](#)
- o [MEQc10 | Garage pollutant protection](#)
- o [MEQc11 | Environmental tobacco smoke \(ETS\) control in mid-rise buildings](#)
- o [MEQc12 | Compartmentalization of units in mid-rise buildings](#)
- o [MEQc2 | Combustion venting in mid-rise buildings](#)
- o [MEQc4 | Outdoor air ventilation in mid-rise buildings](#)
- o [MEQc5 | Local exhaust in mid-rise buildings](#)
- o [MEQc8 | Contaminant control in mid-rise buildings](#)



Our "watch" feature allows you to stay current on all aspects of this specific credit. In your account, you can control what you get updated on and how you receive your notifications. [Hide](#)

LEED O+M: Existing Buildings | v4 - LEED v4

Interior lighting

Possible 2 points

1 result in All .

- [Glossary](#)

Intent

To promote occupants' productivity, comfort, and well-being by providing high-quality lighting.

Requirements

Establishment

Option 1. Lighting control (1 point)

For at least 50% of individual occupant spaces, have in place individual lighting controls that enable occupants to adjust the lighting to suit their individual tasks and preferences, with at least three lighting levels or scenes (on, off, midlevel). Midlevel is 30% to 70% of the maximum illumination level (not including daylight contributions).

For all shared multi-occupant spaces, meet all of the following requirements.

- Have in place multizone control systems that enable occupants to adjust the lighting to meet group needs and preferences, with at least three lighting levels or scenes (on, off, midlevel).
- Lighting for any presentation or projection wall must be separately controlled.
- Switches or manual controls must be located in the same space as the controlled luminaires. A person operating the controls must have a direct line of sight to the controlled luminaires.

AND/OR

Option 2. Lighting quality (1 point)

Choose four of the following strategies.

1. For all regularly occupied spaces, have in place light fixtures with a luminance of less than 2,500cd/m² between 45 and 90 degrees from nadir. Exceptions include wallwash fixtures properly aimed at walls, as specified by manufacturer's data, indirect uplighting fixtures, provided there is no view down into these uplights from a regularly occupied space above, and any other specific applications (i.e. adjustable fixtures).
2. For the entire project, have in place light sources with a CRI of 80 or higher. Exceptions include lamps or fixtures specifically designed to provide colored lighting for effect, site lighting, or other special use.
3. For at least 75% of the total connected lighting load, have in place light sources that have a rated life (or L70 for LED sources) of at least 24,000 hours (at 3-hour per start, if applicable).
4. Have in place direct-only overhead lighting for 25% or less of the total connected lighting load for all regularly occupied spaces.
5. For at least 90% of the regularly occupied floor area, meet or exceed the following thresholds for area-weighted average surface reflectance: 85% for ceilings, 60% for walls, and 25% for floors.
6. Meet or exceed the following thresholds for area-weighted average surface reflectance: 45% for work surfaces and 50% for movable partitions.
7. For at least 75% of the regularly occupied floor area, meet ratio of average wall surface [illuminance](#) (excluding fenestration) to average work surface illuminance that does not exceed 1:10. Must also meet strategy E, strategy F, or demonstrate area-weighted surface reflectance of at least 60% for walls.
8. For at least 75% of the regularly occupied floor area, meet ratio of average ceiling illuminance (excluding fenestration) to work surface illuminance that does not exceed 1:10. Must also meet strategy E, strategy F, or demonstrate area-weighted surface reflectance of at least 85% for ceilings.
9. [\[India ACP: Interior Lighting\]](#)

Performance

None.

Alternative Compliance Paths (ACPs)

India ACP: Interior Lighting

I. Projects in India may, in all regularly occupied spaces, meet or exceed the lower [illuminance](#) levels listed in the Bureau of Indian Standards (BIS) code -- IS 3646 (Part 1): 1992, Table 1- Recommended Illumination.