

[USGBC Home](#)

- [Credits](#)
- [Pilot credits](#)
 - [Awareness & education](#)
 - [Energy & atmosphere](#)
 - [Indoor environmental quality](#)
 - [Innovation & design process](#)
 - [Location & linkages](#)
 - [Material & resources](#)
 - [Sustainable sites](#)
 - [Water efficiency](#)
- [EQpc22 | Interior lighting - quality](#)
 - [EAp27 | Reconcile projected and actual energy performance](#)
 - [EAp27 | Reconcile projected and actual energy performance](#)
 - [EAp3 | Medical and process equipment efficiency](#)
 - [EAp3 | Medical and process equipment efficiency](#)
 - [EAp38 | Advanced utility tracking](#)
 - [EAp56 | Renewable energy - distributed generation](#)
 - [EAp56 | Renewable energy - distributed generation](#)
 - [EAp59 | Occupant engagement](#)
 - [EAp59 | Occupant engagement](#)
 - [EAp65 | Monitoring based commissioning](#)
 - [EAp66 | Community contaminant prevention - airborne releases](#)
 - [EAp66 | Community contaminant prevention - airborne releases](#)
 - [EAp67 | Pilot alternative compliance path - EAp2 Energy Jumpstart](#)
 - [EAp67 | Pilot alternative compliance path - EAp2 Energy Jumpstart](#)
 - [EAp71 | Performance of ENERGY STAR for Homes](#)
 - [EAp72 | Active solar-ready design](#)
 - [EAp73 | HVAC Start-up credentialing](#)
 - [EAp73 | HVAC Start-up credentialing](#)
 - [EAp8 | Demand response](#)
 - [EAp8 | Demand response](#)
 - [EAp86 | LEED 2009 EBOM ACPs for ISO 50001](#)
 - [EAp92 | EA Pilot ACP: Advanced Buildings™ New Construction Guide](#)
 - [EQpc21 | Low-emitting interiors](#)
 - [EQpc22 | Interior lighting - quality](#)
 - [EQpc22 | Interior lighting - quality](#)
 - [EQpc24 | Acoustics](#)
 - [EQpc44 | Ergonomics strategy](#)
 - [EQpc44 | Ergonomics strategy](#)
 - [EQpc44 | Ergonomics strategy](#)
 - [EQpc47 | Acoustic comfort](#)
 - [EQpc47 | Acoustic comfort](#)
 - [EQpc57 | Enhanced acoustical performance - exterior noise control](#)
 - [EQpc57 | Enhanced acoustical performance - exterior noise control](#)
 - [EQpc68 | Indoor air quality procedure - alternative compliance path](#)
 - [EQpc68 | Indoor air quality procedure - alternative compliance path](#)
 - [EQpc68 | Indoor air quality procedure - alternative compliance path](#)
 - [EQpc74 | No environmental tobacco smoke](#)
 - [EQpc78 | Design for active occupants](#)
 - [EQpc78 | Design for active occupants](#)
 - [EQpc78 | Design for active occupants](#)
 - [EQpc85 | Learning Controls for Thermal Comfort](#)
 - [EQpc85 | Learning Controls for Thermal Comfort](#)
 - [GIBpc10 | Sustainable wastewater management](#)
 - [IDpc28 | Trades training](#)
 - [IDpc60 | Integrative process](#)
 - [IDpc60 | Integrative process](#)
 - [IPpc81 | Green training for contractors, trades, operators and service workers](#)
 - [IPpc81 | Green training for contractors, trades, operators and service workers](#)
 - [IPpc81 | Green training for contractors, trades, operators and service workers](#)
 - [IPpc88 | LEED O+M Starter Kit](#)
 - [IPpc88 | LEED O+M Starter Kit](#)
 - [IPpc89 | Social equity within the community](#)
 - [IPpc89 | Social equity within the community](#)
 - [IPpc90 | Social equity within the project team](#)
 - [IPpc90 | Social equity within the project team](#)
 - [IPpc91 | Social equity within the supply chain](#)
 - [IPpc91 | Social equity within the supply chain](#)
 - [IPpc93 | Prevention through Design](#)
 - [IPpc93 | Prevention through Design](#)
 - [LLpc30 | Bicycle Network and Storage](#)
 - [LLpc9 | Street network](#)
 - [LTpc70 | Green vehicles](#)
 - [MRpc34 | Design for adaptability](#)
 - [MRpc34 | Design for adaptability](#)
 - [MRpc52 | Material multi-attribute assessment](#)
 - [MRpc52 | Material multi-attribute assessment](#)
 - [MRpc53 | Responsible sourcing of raw materials](#)
 - [MRpc53 | Responsible sourcing of raw materials](#)
 - [MRpc54 | Avoidance of chemicals of concern](#)
 - [MRpc54 | Avoidance of chemicals of concern](#)
 - [MRpc61 | Material disclosure and assessment](#)
 - [MRpc62 | Disclosure of chemicals of concern](#)
 - [MRpc63 | Whole building life cycle assessment](#)
 - [MRpc69 | Construction and demolition waste management](#)
 - [MRpc76 | Material ingredient reporting](#)
 - [MRpc76 | Material ingredient reporting](#)

- [MRpc77 | Material ingredient optimization](#)
- [MRpc79 | Material ingredients product manufacturer supply chain optimization](#)
- [MRpc79 | Material ingredients product manufacturer supply chain optimization](#)
- [MRpc79 | Material ingredients product manufacturer supply chain optimization](#)
- [MRpc80 | Environmentally preferable interior finishes and furnishings](#)
- [MRpc80 | Environmentally preferable interior finishes and furnishings](#)
- [MRpc84 | MR Credit Category Pilot ACP](#)
- [MRpc87 | Verified Construction & Demolition Recycling Rates](#)
- [MRpc87 | Verified Construction & Demolition Recycling Rates](#)
- [MRpc87 | Verified Construction & Demolition Recycling Rates](#)
- [SSpc14 | Walkable project site](#)
- [SSpc14 | Walkable project site](#)
- [SSpc16 | Rainwater management](#)
- [SSpc16 | Rainwater management](#)
- [SSpc45 | Site assessment](#)
- [SSpc55 | Bird collision deterrence](#)
- [SSpc55 | Bird collision deterrence](#)
- [SSpc55 | Bird collision deterrence](#)
- [SSpc64 | Site improvement plan](#)
- [SSpc7 | Light pollution reduction](#)
- [SSpc7 | Light pollution reduction](#)
- [SSpc75 | Clean construction](#)
- [SSpc75 | Clean construction](#)
- [SSpc75 | Clean construction](#)
- [SSpc82 | Local food production](#)
- [SSpc82 | Local food production](#)
- [SSpc82 | Local food production](#)
- [SSpc82 | Local food production](#)
- [SSpc83 | Site development - protect or restore habitat - alternative compliance path](#)
- [SSpc83 | Site development - protect or restore habitat - alternative compliance path](#)
- [SSpc83 | Site development - protect or restore habitat - alternative compliance path](#)
- [SSpc83 | Site development - protect or restore habitat - alternative compliance path](#)
- [WEpc10 | Sustainable wastewater management](#)
- [WEpc10 | Sustainable wastewater management](#)
- [WEpc17 | Cooling tower water use](#)
- [WEpc17 | Cooling tower water use](#)
- [WEpc18 | Appliance and process water use reduction](#)
- [WEpc18 | Appliance and process water use reduction](#)
- [WEpc18 | Appliance and process water use reduction](#)
- [WEpc32 | WaterSense for new homes](#)
- [WEpc32 | WaterSense for new homes](#)
- [WEpc94 | No Cooling Tower - alternative compliance path](#)
- [WEpc94 | No Cooling Tower - alternative compliance path](#)
- [WEpc94 | No Cooling Tower - alternative compliance path](#)

Our "watch" feature allows you to stay current on all aspects of this specific credit. In your account, you can control what you get updated on and how you receive your notifications. [Hide](#)

| v3 - LEED 2009

Interior lighting - quality

EQpc22 | Possible 1 point

1 result in All .

- [Glossary](#)

Intent

Pilot Credit Closed

This pilot credit is closed to new registrations

Provide for occupant comfort by establishing quality criteria for interior lighting within a space.

Requirements

* This credit language is drawn from the LEED v4 draft. Where other point totals are noted, this pilot credit is worth 1 point in total. *

Establishment

Option 2. Lighting quality (1 point)

Choose four of the following strategies.

- For all regularly occupied spaces, have in place light fixtures with a luminance of less than 2,500cd/m² between 45 and 90 degrees from nadir. Exceptions include wallwash fixtures properly aimed at walls, as specified by manufacturer's data, indirect uplighting fixtures, provided there is no view down into these uplights from a regularly occupied space above, and any other specific applications (i.e. adjustable fixtures).
- For the entire project, have in place light sources with a CRI of 80 or higher. Exceptions include lamps or fixtures specifically designed to provide colored lighting for effect, site lighting, or other special use.
- For at least 75% of the total connected lighting load, have in place light sources that have a rated life (or L70 for LED sources) of at least 24,000 hours (at 3-hour per start, if applicable).
- Have in place direct-only overhead lighting for 25% or less of the total connected lighting load for all regularly occupied spaces.
- For at least 90% of the regularly occupied floor area, meet or exceed the following thresholds for area-weighted average surface reflectance: 85% for ceilings, 60% for walls, and 25% for floors.
- Meet or exceed the following thresholds for area-weighted average surface reflectance: 45% for work surfaces and 50% for movable partitions.
- For at least 75% of the regularly occupied floor area, meet ratio of average wall surface [illuminance](#) (excluding fenestration) to average work surface illuminance that does not exceed 1:10. Must also meet strategy E, strategy F, or demonstrate area-weighted surface reflectance of at least 60% for walls.
- For at least 75% of the regularly occupied floor area, meet ratio of average ceiling illuminance (excluding fenestration) to work surface illuminance that does not exceed 1:10. Must also meet strategy E, strategy F, or demonstrate area-weighted surface reflectance of at least 85% for ceilings.

Performance

None.

General Pilot Documentation Requirements

[Register for the pilot credit](#)

- Participate in the [LEEDuser pilot credit forum](#)
- Complete the feedback survey:

[Credits 1-14](#)

[Credits 15-27](#)

[Credits 28-42](#)

[Credits 43-56](#)

[Credits 57-67](#)

[Credits 68-82](#)

[Credits 83-103](#)

Credit specific

Note: the below submittals are suggestions, alternative forms of documentation or calculation strategies will be accepted.

1. For strategy A, a list of all light fixtures used in the regularly occupied spaces. For each fixture, provide a description, manufacturer name, and indicate whether the fixture has a luminance of less than 2,500cd/m² between 45 and 90 degrees from nadir. Also indicate whether there are any fixtures excluded and whether they are an approved exception.
2. For strategy B, a list of all light sources included in the interior spaces of the project. For each light source, provide a description, light source type, manufacturer or vendor name, and CRI value. Also indicate whether there are any light sources excluded and whether they are an approved exception.
3. For strategy C,
 1. A list of all light sources included in the project. For each light source, provide a description, light source type, manufacturer or vendor name, total connected lighting load, and rated life value.
 2. Calculation for the percent of connected lighting load that meets rated life criteria.
4. For strategy D,
 1. A list of all light fixtures used in the regularly occupied spaces. For each fixture, provide a description, manufacturer name, total connected lighting load, and indicate whether the fixture is direct-only overhead lighting.
 2. Calculation for the percent of connected lighting load that is associated with direct-only overhead lighting.
5. For strategy E,
 1. Indicate whether any regularly occupied spaces are being excluded from the credit requirements and the associated floor area.
 2. A list of all surfaces in the regularly occupied spaces that are being included in the credit requirements. For each surface, provide a description, manufacturer or vendor name, reflectance value and the percent of the overall ceiling area, wall area, or floor area that uses the surface.
 3. Calculation for average surface reflectance for ceiling area, wall area, and floor area. The calculation should be area- weighted, based on the percentages provided in the surface list. Only 1 calculation for each surface type is needed, the calculations do not need to be performed on a space-by-space basis.
 4. Description of methods used to determine reflectance values.
6. For strategy F,
 1. A list of all work surfaces and moveable partitions in the project.
 2. For each surface, provide a description, manufacturer or vendor name, reflectance value and the percent of the overall work surface area, or overall moveable partition surface area that is attributed to the surface.
 3. Calculation for average surface reflectance for work surfaces, or moveable partitions. The calculation should be area- weighted, based on the percentages provided in the surface list. Only 1 calculation for each surface type is needed, the calculations do not need to be performed on a space-by-space basis.
 4. Description of methods used to determine reflectance values.
7. For strategy G,
 1. A list that includes representative areas for all regularly occupied spaces in the project. For each area, include an area description, area location(s), work plane description, work plane [illuminance](#) value, wall surface illuminance value, and a calculation for work plane illuminance to wall surface illuminance (in the format of 1: X).
 2. Calculation for the average ratio.
 3. Demonstration that the project also meets strategy E, strategy F, or has area-weighted surface reflectance of 60% for walls.
 4. Description of methods used to determine illuminance values.
8. For strategy H,
 1. A list that includes representative areas for all regularly occupied spaces in the project. For each area, include an area description, area location(s), work plane description, work plane illuminance value, wall surface illuminance value, and a calculation for work plane illuminance to ceiling surface illuminance (in the format of 1: X).
 2. Calculation for the average ratio.
 3. Demonstration that the project also meets strategy E, strategy F, or has area-weighted surface reflectance of 85% for ceilings.
 4. Description of methods used to determine illuminance values.

Additional questions:

1. Do the criteria associated with quality interior lighting align with your project's and occupants comfort and productivity needs?
2. How difficult was it to document this credit? Is there anything that could be changed to make it easier to document?

Changes

- Changes made for 2nd Public Comment (08/01/2011):
 - Added energy efficiency requirement
 - Broke out bullet points into hardware and design categories
 - Clarified equations
- Changes made for 3rd Public Comment (03/01/2012):
 - Copyedited language
 - Added EB: O+M path to the Pilot Library
- Changes made for 5th Public Comment (01/15/2013):
 - Updated with LEED v4 5th Public Comment changes
- Changes made (04/15/2013):
 - Submittals updated to align with v4 language revisions

0 comments [Leave a comment](#)

Leave a comment Don't have an account? [Create one](#)

You must be signed in to leave a comment.

Email

Password

