

- [Credits](#)
- [Pilot credits](#)
 - [Awareness & education](#)
 - [Energy & atmosphere](#)
 - [Indoor environmental quality](#)
 - [Innovation & design process](#)
 - [Location & linkages](#)
 - [Material & resources](#)
 - [Sustainable sites](#)
 - [Water efficiency](#)
- [MRpc34 | Design for adaptability](#)
 - [EAp27 | Reconcile projected and actual energy performance](#)
 - [EAp27 | Reconcile projected and actual energy performance](#)
 - [EAp3 | Medical and process equipment efficiency](#)
 - [EAp3 | Medical and process equipment efficiency](#)
 - [EAp38 | Advanced utility tracking](#)
 - [EAp56 | Renewable energy - distributed generation](#)
 - [EAp56 | Renewable energy - distributed generation](#)
 - [EAp59 | Occupant engagement](#)
 - [EAp59 | Occupant engagement](#)
 - [EAp65 | Monitoring based commissioning](#)
 - [EAp66 | Community contaminant prevention - airborne releases](#)
 - [EAp66 | Community contaminant prevention - airborne releases](#)
 - [EAp67 | Pilot alternative compliance path - EAp2 Energy Jumpstart](#)
 - [EAp67 | Pilot alternative compliance path - EAp2 Energy Jumpstart](#)
 - [EAp71 | Performance of ENERGY STAR for Homes](#)
 - [EAp72 | Active solar-ready design](#)
 - [EAp73 | HVAC Start-up credentialing](#)
 - [EAp73 | HVAC Start-up credentialing](#)
 - [EAp8 | Demand response](#)
 - [EAp8 | Demand response](#)
 - [EAp86 | LEED 2009 EBOM ACPs for ISO 50001](#)
 - [EAp92 | EA Pilot ACP: Advanced Buildings™ New Construction Guide](#)
 - [EQpc21 | Low-emitting interiors](#)
 - [EQpc22 | Interior lighting - quality](#)
 - [EQpc22 | Interior lighting - quality](#)
 - [EQpc24 | Acoustics](#)
 - [EQpc44 | Ergonomics strategy](#)
 - [EQpc44 | Ergonomics strategy](#)
 - [EQpc44 | Ergonomics strategy](#)
 - [EQpc47 | Acoustic comfort](#)
 - [EQpc47 | Acoustic comfort](#)
 - [EQpc57 | Enhanced acoustical performance - exterior noise control](#)
 - [EQpc57 | Enhanced acoustical performance - exterior noise control](#)
 - [EQpc68 | Indoor air quality procedure - alternative compliance path](#)
 - [EQpc68 | Indoor air quality procedure - alternative compliance path](#)
 - [EQpc68 | Indoor air quality procedure - alternative compliance path](#)
 - [EQpc74 | No environmental tobacco smoke](#)
 - [EQpc78 | Design for active occupants](#)
 - [EQpc78 | Design for active occupants](#)
 - [EQpc78 | Design for active occupants](#)
 - [EQpc85 | Learning Controls for Thermal Comfort](#)
 - [EQpc85 | Learning Controls for Thermal Comfort](#)
 - [GIBpc10 | Sustainable wastewater management](#)
 - [IDpc28 | Trades training](#)
 - [IDpc60 | Integrative process](#)
 - [IDpc60 | Integrative process](#)
 - [IPpc81 | Green training for contractors, trades, operators and service workers](#)
 - [IPpc81 | Green training for contractors, trades, operators and service workers](#)
 - [IPpc81 | Green training for contractors, trades, operators and service workers](#)
 - [IPpc88 | LEED O+M Starter Kit](#)
 - [IPpc88 | LEED O+M Starter Kit](#)
 - [IPpc89 | Social equity within the community](#)
 - [IPpc89 | Social equity within the community](#)
 - [IPpc90 | Social equity within the project team](#)
 - [IPpc90 | Social equity within the project team](#)
 - [IPpc91 | Social equity within the supply chain](#)
 - [IPpc91 | Social equity within the supply chain](#)
 - [IPpc93 | Prevention through Design](#)
 - [IPpc93 | Prevention through Design](#)
 - [LLpc30 | Bicycle Network and Storage](#)
 - [LLpc9 | Street network](#)
 - [LTpc70 | Green vehicles](#)
 - [MRpc34 | Design for adaptability](#)
 - [MRpc34 | Design for adaptability](#)
 - [MRpc52 | Material multi-attribute assessment](#)
 - [MRpc52 | Material multi-attribute assessment](#)
 - [MRpc53 | Responsible sourcing of raw materials](#)
 - [MRpc53 | Responsible sourcing of raw materials](#)
 - [MRpc54 | Avoidance of chemicals of concern](#)
 - [MRpc54 | Avoidance of chemicals of concern](#)
 - [MRpc61 | Material disclosure and assessment](#)
 - [MRpc61 | Material disclosure and assessment](#)
 - [MRpc62 | Disclosure of chemicals of concern](#)
 - [MRpc62 | Disclosure of chemicals of concern](#)
 - [MRpc63 | Whole building life cycle assessment](#)
 - [MRpc69 | Construction and demolition waste management](#)
 - [MRpc76 | Material ingredient reporting](#)
 - [MRpc76 | Material ingredient reporting](#)
 - [MRpc77 | Material ingredient optimization](#)
 - [MRpc77 | Material ingredient optimization](#)
 - [MRpc79 | Material ingredients product manufacturer supply chain optimization](#)

- [MRpc79 | Material ingredients product manufacturer supply chain optimization](#)
- [MRpc79 | Material ingredients product manufacturer supply chain optimization](#)
- [MRpc80 | Environmentally preferable interior finishes and furnishings](#)
- [MRpc80 | Environmentally preferable interior finishes and furnishings](#)
- [MRpc84 | MR Credit Category Pilot ACP](#)
- [MRpc87 | Verified Construction & Demolition Recycling Rates](#)
- [MRpc87 | Verified Construction & Demolition Recycling Rates](#)
- [MRpc87 | Verified Construction & Demolition Recycling Rates](#)
- [SSpc14 | Walkable project site](#)
- [SSpc14 | Walkable project site](#)
- [SSpc16 | Rainwater management](#)
- [SSpc16 | Rainwater management](#)
- [SSpc45 | Site assessment](#)
- [SSpc55 | Bird collision deterrence](#)
- [SSpc55 | Bird collision deterrence](#)
- [SSpc55 | Bird collision deterrence](#)
- [SSpc64 | Site improvement plan](#)
- [SSpc7 | Light pollution reduction](#)
- [SSpc7 | Light pollution reduction](#)
- [SSpc75 | Clean construction](#)
- [SSpc75 | Clean construction](#)
- [SSpc75 | Clean construction](#)
- [SSpc82 | Local food production](#)
- [SSpc82 | Local food production](#)
- [SSpc82 | Local food production](#)
- [SSpc82 | Local food production](#)
- [SSpc83 | Site development - protect or restore habitat - alternative compliance path](#)
- [SSpc83 | Site development - protect or restore habitat - alternative compliance path](#)
- [SSpc83 | Site development - protect or restore habitat - alternative compliance path](#)
- [SSpc83 | Site development - protect or restore habitat - alternative compliance path](#)
- [WEpc10 | Sustainable wastewater management](#)
- [WEpc10 | Sustainable wastewater management](#)
- [WEpc17 | Cooling tower water use](#)
- [WEpc17 | Cooling tower water use](#)
- [WEpc18 | Appliance and process water use reduction](#)
- [WEpc18 | Appliance and process water use reduction](#)
- [WEpc18 | Appliance and process water use reduction](#)
- [WEpc32 | WaterSense for new homes](#)
- [WEpc32 | WaterSense for new homes](#)



Our "watch" feature allows you to stay current on all aspects of this specific credit. In your account, you can control what you get updated on and how you receive your notifications. [Hide](#)

LEED BD+C: Multifamily Midrise | v3 - LEED 2008

Design for adaptability

MRpc34 | Possible 1 point

1 result in All .

- [Glossary](#)

Intent

To reduce the materials needed for and waste produced from future maintenance, repair, renovation and rehabilitation through structural, mechanical, and user-induced design.

Requirements

HOMES

Note: Multi-family projects required to meet the Fair Housing Amendments Act (FHAA) (e.g., a building with ≥ 4 residential units and an elevator) may earn points in Option 1 if they have twice the number of accessible units that meet FHAA requirements than what is required by code.

Option 1. Universal design features

Meet all of the following:

1. Zero-Step Main Entrance: Entrances with no abrupt change in level must provide access to dwelling units and site amenities.
2. Accessible Doorway: A doorway must have a minimum clear width of open doorway of 32 inches and clear maneuvering space inside and outside the door.
3. Accessible Passage: An accessible route is a path that is at least 36 inches wide, smooth, as level as possible, and without hazards or obstructions.
4. Adaptable bathroom: Bathroom must have a minimum 30 inch x 48 inch clear floor space and standard accessible shower and toilet fixtures.
5. Accessible HVAC and lighting controls: Controls such as thermostats and other heating, air-conditioning, and ventilation mechanisms as well as light switches and electrical outlets must be positioned no less than 15 inches from the floor and no higher than 48 inches with no access obstructions.
6. A kitchen, dining area, living area, adaptable full bathroom, and bedroom on the accessible level.

AND/OR

Option 2. Open building structural systems

Allow for easy redefining of rooms/floorplans with minimal renovation and material waste. Meet both of the following:

1. Centralized primary structural elements (such as "clear-span" structural design and partitions)
2. Flexible ceiling or floor systems (such as suspended ceilings, open-web floor trusses, raised or plenum floors)

AND/OR

Option 3. Organized and accessible MEP systems

Meet one of the following:

1. Stacked plumbing, electrical and mechanical design. Stacked or adjacent MEP layouts locate functional areas (like bathrooms, kitchens, and laundry areas for plumbing lines) vertically from floor to floor or in shared common walls on the same floor to provide access for installation and repairs, reduce redundant supply and space requirements, and ensure adaptable use of nonMEP spaces
2. Separation of MEP systems from within exterior walls and primary interior structural members

MID-RISE

Projects required to meet the Fair Housing Amendments Act (FHAA) (e.g., a building with ≥ 4 residential units and an elevator) may earn points in if they have twice the number of accessible units that meet FHAA requirements than what is required by code.

Universal design features

Meet all of the following:

1. Zero-Step Main Entrance: Entrances with no abrupt change in level must provide access to dwelling units and site amenities.
2. Accessible Doorway: A doorway must have a minimum clear width of open doorway of 32 inches and clear maneuvering space inside and outside the door.
3. Accessible Passage: An accessible route is a path that is at least 36 inches wide, smooth, as level as possible, and without hazards or obstructions.
4. Adaptable bathroom: Bathroom must have a minimum 30 inch x 48 inch clear floor space and standard accessible shower and toilet fixtures.
5. Accessible HVAC and lighting controls: Controls such as thermostats and other heating, air-conditioning, and ventilation mechanisms as well as light switches and electrical outlets must be positioned no less than 15 inches from the floor and no higher than 48 inches with no access obstructions.
6. A kitchen, dining area, living area, adaptable full bathroom, and bedroom on the accessible level.

General Pilot Documentation Requirements

[Register for the pilot credit](#)

- Participate in the [LEEDuser pilot credit forum](#)
- Complete the feedback survey:

[Credits 1-14](#)

[Credits 15-27](#)

[Credits 28-42](#)

[Credits 43-56](#)

[Credits 57-67](#)

[Credits 68-82](#)

[Credits 83-103](#)

LEED for Homes Review Process

LEED for Homes projects: When complete, [submit documentation here](#).

0 comments[Leave a comment](#)

Leave a comment Don't have an account? [Create one](#)

You must be signed in to leave a comment.

Email

Password