Please upgrade your browser. This site requires a newer version to work correctly. Read more

- WEc2 | Irrigation system
- WEc2 | Innovative wastewater technologies
- WEc2 | Innovative wastewater technologies
- WEc2 | Innovative wastewater technologies
- WEc2 | Innovative wastewater technologies
- WEc2 | Innovative wastewater technologies
- WEc2 | Innovative wastewater technologies
- WEc2 | Innovative wastewater technologies
- WEc2 | Indoor water use
- WEc2 | Innovative wastewater treatment and reuse
- WEc2.1 | Additional indoor plumbing fixture and fitting efficiency
- WEc2.2 | Additional indoor plumbing fixture and fitting efficiency
- WEc2.3 | Additional indoor plumbing fixture and fitting efficiency
- WEc3 | Indoor water use
- WEc3 | Water efficient landscaping
- WEc3 | Outdoor water use
- WEc3 | Water use reduction
- WEc3 | Water use reduction
- WEc3 | Water use reduction
- WEc3 | Water use reduction
- WEc3 | Water use reduction
- WEc3.1 | Water use reduction - 20% reduction
- WEc3.1 | Water efficient landscaping
- WEc3.1 | Water use reduction
- WEc3.1 | Water use reduction - 20% reduction
- WEc3.1 | Water use reduction - 20% reduction
- WEc3.1 | Water use reduction - 20% reduction
- WEc3.1 | Water use reduction: 20% reduction
- WEc3.1-3.2 | Water use reduction
- WEc3.2 | Water use reduction - 30% reduction
- WEc3.2 | Water use reduction - 30% or 40% reduction
- WEc3.2 | Water use reduction - 30% reduction
- WEc3.2 | Water use reduction - 30% reduction
- WEc3.2 | Water use reduction
- WEc3.2 | Water efficient landscaping
- WEc3.2 | Water use reduction: 30% Reduction
- WEc3.3 | Water efficient landscaping
- WEc4 | Cooling tower water management
- WEc4 | Process water use reduction
- WEc4 | Process water use reduction
- WEc4.1 | Water use reduction - building equipment
- WEc4.1 | Cooling tower water management
- WEc4.2 | Cooling tower water management
- WEc4.2 | Water use reduction - cooling towers
- WEc4.3 | Water use reduction - food waste systems
- WEp1 | Water use reduction
- WEp1 | Minimum indoor plumbing fixture and fitting efficiency
- WEp1 | Minimum water efficiency
- WEp1 | Water metering
- WEp1 | Minimum indoor plumbing fixture and fitting efficiency
- WEp1 | Water use reduction
- WEp1 | Water use reduction
- WEp1 | Water use reduction
- WEp1 | Water use reduction
- WEp1 | Water use reduction
- WEp1 | Water use reduction
- WEp1 | Water use reduction
- WEp2 | Discharge water compliance
- WEp2 | Minimize potable water use for medical equipment cooling
- WEp2 | Discharge water compliance

Our "watch" feature allows you to stay current on all aspects of this specific credit. In your account, you can control what you get updated on and how you receive your notifications. Hide

**LEED O+M: Data Centers | v4 - LEED v4**

# Cooling tower water use

## Possible 4 points

**1** result in**All** .

- Glossary

### Intent

To conserve water used for cooling tower makeup while controlling microbes, corrosion, and scale in the condenser water system.

### Requirements

#### Establishment

For cooling towers and evaporative condensers, conduct a potable water analysis within five years of submission for certification, measuring at least the five control parameters listed in Table 1.

**Table 1. Maximum concentrations for parameters in condenser water**

| Parameter | Maximum level |
|---|---|
| Ca (as $CaCO_3$) | 1000 ppm |
| Total alkalinity | 1000 ppm |
| $SiO_2$ | 100 ppm |
| $Cl^-$ | 250 ppm |
| Conductivity | 2000 µS/cm |

ppm = parts per million
µS/cm = micro siemens per centimeter

Calculate the number of cooling tower cycles by dividing the maximum allowed concentration level of each parameter by the actual concentration level of each parameter found in the potable makeup water. Limit cooling tower cycles to avoid exceeding maximum values for any of these parameters.

**Table 2. Points for cooling tower cycles**

| Cooling tower cycles | Points (except data centers) | Points (data centers) |
|---|---|---|
| Maximum number of cycles achieved without exceeding any filtration levels or affecting operation of condenser water system (up to maximum of 10 cycles) | 2 | 2 |
| Achieve a minimum 10 cycles by increasing the level of treatment in condenser or make-up water<br>OR Achieve the number of cycles for 1 point and use a minimum 20% recycled nonpotable water | 3 | 4 |

**Performance**

None

**Pilot Alternative Compliance Path available**

A pilot alternative compliance path is available for this credit to certain project types without cooling towers. For more information, please visit the Pilot Credit Library

Pilot ACPs:
No Cooling Tower - alternative compliance path (BD+C)
No Cooling Tower - alternative compliance path (O+M)
No Cooling Tower - alternative compliance path (O+M: Data Centers)