Please upgrade your browser. This site requires a newer version to work correctly. Read more
Our "watch" feature allows you to stay current on all aspects of this specific credit. In your account, you can control what you get updated on and how you receive your notifications. Hide

LEED BD+C: Homes | v4 - LEED v4

Access to transit

Possible 2 points

1 result in**All** .

Intent

To reduce pollution and land development effects from automobile use.

Requirements

Locate the project within a ¼-mile (400 meter) walking distance of bus or streetcar stops, or within a ½-mile (800 meter)walking distance of bus rapid transit stops, light or heavy rail stations, or ferry terminals. The transit service at those stops in aggregate must meet the minimums listed in Table 1 or Table 2.

- A bus or streetcar stop must serve a route that extends in opposite directions; the walking distance can be the average distance to the two stops.
- A single stop that serves as the terminal for a transit route can be counted.
- Trips in opposite directions are counted separately.
- Only one stop per route in a given direction can be counted.

Table 1. Minimum daily transit service for projects with multiple transit types (bus, streetcar, rail, or ferry)

Weekday trips	Weekend trips	Points
72	40	1
144	108	1.5
360	216	2

Table 2. Minimum daily transit service for projects with commuter rail or ferry service only

Weekday trips	Points
24	1
40	1.5
60	2