



- [EQ118 | Interior lighting](#)
- [EQ119 | Interior lighting](#)
- [EQ120 | Interior lighting](#)
- [EQ120 | Interior lighting](#)
- [EQ121 | Daylight](#)
- [EQ121 | Daylight](#)
- [EQ121 | Daylight](#)
- [EQ121 | Daylight](#)
- [EQ121 | Daylight](#)
- [EQ122 | Daylight and quality views](#)
- [EQ122 | Daylight and quality views](#)
- [EQ123 | Quality views](#)
- [EQ123 | Quality Views](#)
- [EQ123 | Quality Views](#)
- [EQ123 | Quality views](#)
- [EQ123 | Quality views](#)
- [EQ124 | Acoustic performance](#)
- [EQ124 | Acoustic performance](#)
- [EQ125 | Green cleaning - custodial effectiveness assessment](#)
- [EQ126 | Green cleaning - products and materials](#)
- [EQ127 | Green cleaning - equipment](#)
- [EQ128 | Integrated pest management](#)
- [EQ129 | Occupant comfort survey](#)
- [EQ131 | Acoustic Performance](#)
- [EQ2.1 | Construction indoor air quality management plan](#)
- [EQ2.2 | Construction indoor air quality assessment](#)
- [EQ3.1 | High performance green cleaning program](#)
- [EQ3.2 | Custodial effectiveness assessment](#)
- [EQ3.3 | Sustainable purchasing of cleaning products and materials](#)
- [EQ3.4 | Sustainable purchasing of cleaning equipment](#)
- [EQ3.5 | Indoor chemical and pollutant source control](#)
- [EQ3.6 | Indoor integrated pest management](#)
- [EQ4 | Low-emitting interiors](#)
- [EQ5.1 | Occupant comfort survey](#)
- [EQ5.2 | Documenting productivity impacts](#)
- [EQ6.1 | Thermal comfort - design](#)
- [EQ6.2 | Thermal comfort - controllability](#)
- [EQ6.3 | Thermal comfort - verification](#)
- [EQ6.4 | Mold prevention](#)
- [EQ7.1 | Interior lighting - design](#)
- [EQ7.2 | Interior lighting - controllability](#)
- [EQ8 | Daylight](#)
- [EQ9 | Quality views](#)
- [EQ907 | Acoustic performance](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | EPA Indoor airPLUS](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Carbon dioxide \(CO2\) monitoring](#)
- [EQc1 | Carbon dioxide \(CO2\) monitoring](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Enhanced ventilation](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1 | Outdoor air delivery monitoring](#)
- [EQc1.1 | Indoor air quality best management practices - indoor air quality management program](#)
- [EQc1.1 | IAQ best management practices - IAQ management program](#)
- [EQc1.2 | Indoor air quality best management practices - outdoor air delivery monitoring](#)
- [EQc1.2 | IAQ best management practices - outdoor air delivery monitoring](#)
- [EQc1.3 | Indoor air quality best management practices - increased ventilation](#)
- [EQc1.3 | IAQ best management practices - increased ventilation](#)
- [EQc1.4 | Indoor air quality best management practices - reduce particulates in air distribution](#)
- [EQc1.4 | IAQ best management practices - reduce particulates in air distribution](#)
- [EQc1.5 | Indoor air quality best management practices - indoor air quality management for facility additions and alterations](#)
- [EQc1.5 | IAQ best management practices - management for facility alterations and additions](#)
- [EQc10 | Garage pollutant protection](#)
- [EQc10 | Mold prevention](#)
- [EQc10 | Mold prevention](#)
- [EQc10.1 | Green cleaning - entryway systems](#)
- [EQc10.2 | Green cleaning - isolation of janitorial closets](#)
- [EQc10.3 | Green cleaning - low environmental impact cleaning policy](#)
- [EQc10.4 | Green cleaning - low environmental impact pest management policy](#)
- [EQc10.5 | Green cleaning - low environmental impact pest management policy](#)
- [EQc10.6 | Green cleaning - low environmental impact cleaning equipment policy](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Combustion venting](#)
- [EQc2 | Acoustic environment](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Ventilation effectiveness](#)
- [EQc2 | Increase ventilation effectiveness](#)
- [EQc2 | Contaminant control](#)
- [EQc2 | Contaminant control](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2 | Increased ventilation](#)
- [EQc2.1 | Occupant comfort - occupant survey](#)
- [EQc2.1 | Occupant comfort - occupant survey](#)
- [EQc2.2 | Controllability of systems - lighting](#)

- [EQc2.2 | Occupant comfort - occupant-controlled lighting](#)
- [EQc2.3 | Occupant comfort - thermal comfort monitoring](#)
- [EQc2.3 | Occupant comfort - thermal comfort monitoring](#)
- [EQc2.4 | Daylight and views](#)
- [EQc2.4 | Occupant comfort - daylight and views](#)
- [EQc2.5 | Occupant comfort - daylight and views](#)
- [EQc3 | Moisture control](#)
- [EQc3 | Construction IAQ management plan - during construction](#)
- [EQc3 | Construction IAQ management plan](#)
- [EQc3 | Construction IAQ management plan - during construction](#)
- [EQc3 | Balancing of heating and cooling distribution systems](#)
- [EQc3 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Green cleaning - high performance green cleaning program](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Green cleaning - high-performance cleaning program](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan: during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - during construction](#)
- [EQc3.1 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Green cleaning - custodial effectiveness assessment](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.2 | Construction IAQ management plan: before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - after construction](#)
- [EQc3.2 | Construction IAQ management plan - after construction](#)
- [EQc3.2 | Construction IAQ management plan: before occupancy](#)
- [EQc3.2 | Construction IAQ management plan - before occupancy](#)
- [EQc3.3 | Green cleaning - purchase of sustainable cleaning products and materials](#)
- [EQc3.3 | Green cleaning - custodial effectiveness assessment](#)
- [EQc3.4 | Green cleaning - sustainable cleaning equipment](#)
- [EQc3.4 | Green cleaning - purchase of sustainable cleaning products and materials](#)
- [EQc3.5 | Green cleaning - indoor chemical and pollutant source control](#)
- [EQc3.5 | Green cleaning - purchase of sustainable cleaning products and materials](#)
- [EQc3.6 | Green cleaning - indoor integrated pest management](#)
- [EQc3.6 | Green cleaning - purchase of sustainable cleaning products and materials](#)
- [EQc3.7 | Green cleaning - sustainable cleaning equipment](#)
- [EQc3.8 | Green cleaning - entryway systems](#)
- [EQc3.9 | Green cleaning - indoor integrated pest management](#)
- [EQc4 | Outdoor air ventilation](#)
- [EQc4 | Low-emitting materials](#)
- [EQc4 | Low-emitting materials](#)
- [EQc4 | Low-emitting materials](#)
- [EQc4 | Low-emitting materials](#)
- [EQc4 | Enhanced compartmentalization](#)
- [EQc4 | Enhanced compartmentalization](#)
- [EQc4 | Low-emitting materials](#)
- [EQc4 | Low-emitting materials, adhesives and sealants](#)
- [EQc4.1 | Low-emitting materials - adhesives and sealants](#)
- [EQc4.1 | Low-emitting materials - adhesives and sealants](#)
- [EQc4.1 | Low-emitting materials - adhesives and sealants](#)
- [EQc4.1 | Low-emitting materials - adhesives and sealants](#)
- [EQc4.1 | Documenting productivity impacts - absenteeism and health care cost impacts](#)
- [EQc4.1 | Low-emitting materials - adhesives and sealants](#)
- [EQc4.1 | Low-emitting materials - adhesives and sealants](#)
- [EQc4.1 | Low-emitting materials - adhesives and sealants](#)
- [EQc4.1 | Low-emitting materials - adhesives and sealants](#)
- [EQc4.2 | Low-emitting materials - paints and coatings](#)
- [EQc4.2 | Low-emitting materials - paints and coatings](#)
- [EQc4.2 | Low-emitting materials - paints and coatings](#)
- [EQc4.2 | Documenting productivity impacts - other productivity impacts](#)
- [EQc4.2 | Low-emitting materials - paints and coatings](#)
- [EQc4.2 | Low-emitting materials - paints and coatings](#)
- [EQc4.2 | Low-emitting materials - paints and coatings](#)
- [EQc4.2 | Low-emitting materials - paints and coatings](#)
- [EQc4.2 | Low-emitting materials - paints and coatings](#)
- [EQc4.3 | Low-emitting materials - flooring systems](#)
- [EQc4.3 | Low-emitting materials - carpet systems](#)
- [EQc4.3 | Low-emitting materials - carpet systems](#)
- [EQc4.3 | Low-emitting materials - carpet systems](#)
- [EQc4.3 | Low-emitting materials - carpet](#)
- [EQc4.3 | Low-emitting materials - carpet systems](#)
- [EQc4.3 | Low-emitting materials - carpet systems](#)
- [EQc4.3 | Low-emitting materials - flooring systems](#)
- [EQc4.4 | Low-emitting materials - composite wood and agrifiber products](#)
- [EQc4.4 | Low-emitting materials - composite wood and agrifiber products](#)
- [EQc4.4 | Low-emitting materials - composite wood and agrifiber products](#)
- [EQc4.4 | Low-emitting materials - composite wood and agrifiber products](#)
- [EQc4.4 | Low-emitting materials - composite wood and laminate adhesives](#)
- [EQc4.4 | Low-emitting materials - composite wood and agrifiber products](#)
- [EQc4.4 | Low-emitting materials - composite wood](#)
- [EQc4.4 | Low-emitting materials - composite wood](#)
- [EQc4.4 | Low-emitting materials - composite wood and agrifiber products](#)





- o [EQp4.2 | Polychlorinated biphenyl removal](#)
- o [EQp5 | Air filtering](#)
- o [EQp6 | Environmental tobacco smoke](#)
- o [EQp7 | Compartmentalization](#)
- o [MEQc10 | Garage pollutant protection](#)
- o [MEQc11 | Environmental tobacco smoke \(ETS\) control in mid-rise buildings](#)
- o [MEQc12 | Compartmentalization of units in mid-rise buildings](#)
- o [MEQc2 | Combustion venting in mid-rise buildings](#)
- o [MEQc4 | Outdoor air ventilation in mid-rise buildings](#)
- o [MEQc5 | Local exhaust in mid-rise buildings](#)
- o [MEQc8 | Contaminant control in mid-rise buildings](#)



Our "watch" feature allows you to stay current on all aspects of this specific credit. In your account, you can control what you get updated on and how you receive your notifications. [Hide](#)

**LEED BD+C: Core and Shell | v4 - LEED v4**

## Enhanced indoor air quality strategies

### Possible 2 points

1 result in All .

- [Glossary](#)

#### Intent

To promote occupants' comfort, well-being, and productivity by improving indoor air quality.

#### Requirements

##### Option 1. Enhanced IAQ strategies (1 point)

Comply with the following requirements, as applicable.

Mechanically ventilated spaces:

- A. entryway systems;
- B. interior cross-contamination prevention; and
- C. filtration.

Naturally ventilated spaces:

- A. entryway systems; and
- D. natural ventilation design calculations.

Mixed-mode systems:

- A. entryway systems;
- B. interior cross-contamination prevention;
- C. filtration;
- D. natural ventilation design calculations; and
- E. mixed-mode design calculations.

##### A. Entryway systems

Install permanent entryway systems at least 10 feet (3 meters) long in the primary direction of travel to capture dirt and particulates entering the building at regularly used exterior entrances. Acceptable entryway systems include permanently installed grates, grilles, slotted systems that allow for cleaning underneath, rollout mats, and any other materials manufactured as entryway systems with equivalent or better performance. Maintain all on a weekly basis.

##### B. Interior cross-contamination prevention

Sufficiently exhaust each space where hazardous gases or chemicals may be present or used (e.g., garages, housekeeping and laundry areas, copying and printing rooms), using the exhaust rates determined in EQ Prerequisite Minimum Indoor Air Quality Performance or a minimum of 0.50 cfm per square foot (2.54 l/s per square meter), to create negative pressure with respect to adjacent spaces when the doors to the room are closed. For each of these spaces, provide self-closing doors and deck-to-deck partitions or a hard-lid ceiling.

##### C. Filtration

Each ventilation system that supplies outdoor air to occupied spaces must have particle filters or air-cleaning devices that meet one of the following filtration media requirements:

- minimum efficiency reporting value (MERV) of 13 or higher, in accordance with ASHRAE Standard 52.2–2007; or
- Class F7 or higher as defined by CEN Standard EN 779–2002, Particulate Air Filters for General Ventilation, Determination of the Filtration Performance.

Replace all air filtration media after completion of construction and before occupancy.

##### D. Natural ventilation design calculations

Demonstrate that the system design for occupied spaces employs the appropriate strategies in Chartered Institution of Building Services Engineers (CIBSE) Applications Manual AM10, March 2005, Natural Ventilation in Non-Domestic Buildings, Section 2.4.

##### E. Mixed-mode design calculations

Demonstrate that the system design for occupied spaces complies with CIBSE Applications Manual 13–2000, Mixed Mode Ventilation.

##### Option 2. Additional enhanced IAQ strategies (1 point)

Comply with the following requirements, as applicable.

Mechanically ventilated spaces (select one):

- A. exterior contamination prevention;
- B. increased ventilation;
- C. carbon dioxide monitoring; or
- D. additional source control and monitoring.

Naturally ventilated spaces (select one):

- exterior contamination prevention;
- D. additional source control and monitoring; or
- E. natural ventilation room by room calculations.

Mixed-mode systems (select one):

- A. exterior contamination prevention;
- B. increased ventilation;
- D. additional source control and monitoring; or
- E. natural ventilation room-by-room calculations.

**A. Exterior contamination prevention**

Design the project to minimize and control the entry of pollutants into the building. Ensure through the results of computational fluid dynamics modeling, Gaussian dispersion analyses, wind tunnel modeling, or tracer gas modeling that outdoor air contaminant concentrations at outdoor air intakes are below the thresholds listed in Table 1 (or local equivalent for projects outside the U.S., whichever is more stringent).

**Table 1. Maximum concentrations of pollutants at outdoor air intakes**

Pollutants	Maximum concentration	Standard
Those regulated by National Ambient Air Quality Standards (NAAQS)	Allowable annual average OR 8-hour or 24-hour average where an annual standard does not exist OR Rolling 3-month average	National Ambient Air Quality Standards (NAAQS)

**B. Increased ventilation**

Increase breathing zone outdoor air ventilation rates to all occupied spaces by at least 30% above the minimum rates as determined in EQ Prerequisite Minimum Indoor Air Quality Performance.

**C. Carbon dioxide monitoring**

Monitor CO<sub>2</sub> concentrations within all densely occupied spaces. CO<sub>2</sub> monitors must be between 3 and 6 feet (900 and 1 800 millimeters) above the floor. CO<sub>2</sub> monitors must have an audible or visual indicator or alert the building automation system if the sensed CO<sub>2</sub> concentration exceeds the setpoint by more than 10%. Calculate appropriate CO<sub>2</sub> setpoints using methods in ASHRAE 62.1–2010, Appendix C.

**D. Additional source control and monitoring**

For spaces where air contaminants are likely, evaluate potential sources of additional air contaminants besides CO<sub>2</sub>. Develop and implement a materials-handling plan to reduce the likelihood of contaminant release. Install monitoring systems with sensors designed to detect the specific contaminants. An alarm must indicate any unusual or unsafe conditions.

**E. Natural ventilation room-by-room calculations**

Follow CIBSE AM10, Section 4, Design Calculations, to predict that room-by-room airflows will provide effective natural ventilation.

0 comments [Leave a comment](#)

Leave a comment Don't have an account? [Create one](#)

You must be signed in to leave a comment.

Email

Password